

RLK8-800D4-NVR-Kit-IP-Camera-Specifications

	Model	D800
<b>Video &amp; Audio</b>	Image Sensor	1/2.7" CMOS Sensor
	Video Resolution	3840 x 2160 (8.0 Megapixels) at 20 frames/sec
	Lens	f=4.0mm Fixed, F=2.0, with IR Cut
	Video Format	H.264
	Field of View	Horizontal: 87.5°
		Vertical: 47°
	Day & Night	IR-Cut Filter with Auto-Switching
	Night Vision	30 Meters (100ft) (LED: 18pcs/14mil/850nm)
<b>Power</b>	Audio	Audio Recording
	PoE	PoE IEEE 802.3af; 48V Active
	DC Power	DC 12.0V = 1A; < 8W
<b>Interface</b>	Power	DC Power Port
	System	Reset Button
	Ethernet	One 10M/100Mbps RJ45
	Audio	Built-in Microphone
<b>Software Features</b>	Frame Rate	Main Stream: 2fps - 20fps (default: 20fps)
		Sub Stream: 4fps - 15fps (default: 7fps)
	Code Rate	Main Stream: 1024Kbps - 8192Kbps (default: 6144Kbps)
		Sub Stream: 64Kbps - 512Kbps (default: 160Kbps)
	Smart Alarm	Motion-Triggered Alerts
	Protocols & Standards	HTTPS, SSL, TCP/IP, UDP, UPNP, NTP, DHCP, DNS
Backlight Compensation	Support	
Noise Reduction	3D DNR	
<b>Working Environment</b>	Temperature	-10°C - +55°C (14°F - 131°F)
	Humidity	10% - 90%
	Waterproof	IP66
<b>Size &amp; Weight</b>	Dimension	Φ105*93mm
	Weight	385g
<b>Warranty</b>	Limited Warranty <sup>①</sup>	2-Year Limited Warranty. For Support, Visit <a href="https://support.reolink.com/hc/en-us/②">https://support.reolink.com/hc/en-us/②</a>